



Canadyne 18 INCH GULF CONTRACTOR BOOM

Part No. 10175

<u>SPECIFICATION</u>	<u>IMPERIAL</u>	<u>METRIC</u>
Boom Height	19.3 in	490 mm
Freeboard	6.0 in	152 mm
Draft	13.3 in	338 mm
Standard Length	50 ft or 100 ft	15.25 m or 30 m
End Connectors	ASTM-standard extruded aluminum connectors	
Fabric	PVC-coated polyester	
Fabric Weight	22 oz/yd ²	750 g/m ²
Fabric Strip Tensile Strength	400 lbs/in	360kg/5cm
Colour	Orange standard, others available	
Flotation Material / Shape	Cylindrical, closed cell polyethylene foam floats	
Boom Weight	2.0 lbs./ft	3.0 kg/m
Reserve Buoyancy	10 lbs./ft	15 kg/m
Reserve Buoyancy/Weight Ratio	5:1	
Ballast	5/16 in (8.3 mm) Grade 30 galvanised chain	
Ballast Weight	1.12 lbs./ft	1.7 kg/m
Ballast Tensile Strength	8000 lbs.	3640 kg
Secondary Tension Member	PVC Coated 1/4 in (6.3 mm) 7x19 galv. aircraft cable	
Secondary Tension Strength	7000 lbs	3185 kg
Combined Tensile Strength	29,400 lbs.	13,365 kg
Fully Enclosed Chain Pocket	Fully enclosed	

All above values are nominal and subject to change without notice.