



**Canadyne AirBoom MP Model 18/24, 26 PU**

Part No. BMAIUP18/24.26U82MP

<b><u>SPECIFICATION</u></b>	<b><u>IMPERIAL</u></b>	<b><u>METRIC</u></b>
Boom Height	42.0 in	1067 mm
Diameter	18 in	457 mm
Draft	24.0 in	610 mm
Standard Length	82 ft	25 m
Fabric Weight	26 oz/yd <sup>2</sup>	
Fabric	Urethane blend coated Polyester	
Colour	Orange standard, others available	
Boom Weight	3.0 lbs./ft	4.5 kg/m
Buoyancy/Weight Ratio	36.7:1	
Internal Air Chamber Length	16.4 ft	5 m
Separation of Chambers	Internal bulkheads	
Inflation Valve	Monsoon Inflation/Deflation	
End Connectors	ASTM F962-99 extruded marine grade aluminum connector	
Connector Attachment	Boltless, even stress distribution	
Toggle Pins	3/8" (9.5 mm) stainless steel, spring loaded with lanyard	
Ballast	Grade 30, hot galvanized steel chain	
Ballast Size	3/8 in	9.5 mm
Ballast Weight	1.21 lbs./ft	1.8 kg/m
Boom Tensile Strength	48,560 lbs.	22,075 kg
Chain Pocket	Fully enclosed, single layer	
Drain Holes	every 10 feet	every 3 m

All above values are nominal and subject to change without notice.