



Canadyne AirBoom SC Model 8/10, 22 PVC

Part No. BMAIPP08/10.22P82SC

<u>SPECIFICATION</u>	<u>IMPERIAL</u>	<u>METRIC</u>
Boom Height	18.0 in	457 mm
Diameter	8 in	203 mm
Draft	10.0 in	254 mm
Standard Length	82 ft	25 m
Fabric Weight	22 oz/yd ²	
Fabric	PVC coated Polyester	
Colour	Orange standard, others available	
Boom Weight	1.4 lbs./ft	2.0 kg/m
Buoyancy/Weight Ratio	16.3:1	
Separation of Chambers	Single Chamber	
Inflation Valve	Monsoon Inflation/Deflation	
End Connectors	ASTM F962-99 extruded marine grade aluminum connector	
Connector Attachment	Boltless, even stress distribution	
Toggle Pins	3/8" (9.5 mm) stainless steel, spring loaded with lanyard	
Ballast	Grade 30, hot galvanized steel chain	
Ballast Size	9/32 in	7.1 mm
Ballast Weight	0.67 lbs./ft	1.0 kg/m
Boom Tensile Strength	18,500 lbs.	8,410 kg
Chain Pocket	Fully enclosed, single layer	
Drain Holes	every 10 feet	every 3 m

All above values are nominal and subject to change without notice.