



Canadyne Contractor Boom 6/6 22P

Part No. BMCOPP06.06.22IN.50

<u>SPECIFICATION</u>	<u>IMPERIAL</u>	<u>METRIC</u>
Boom Height	12 in	305 mm
Freeboard	6.0 in	152 mm
Draft	6.0 in	153 mm
Standard Length	50 ft	15.25 m
End Connectors	ASTM-standard extruded aluminum connectors	
Skirt Material	PVC-coated polyester	
Skirt Weight	22 oz/yd ²	750 g/m ²
Fabric Strip Tensile Strength	310 lbs	141 kg
Fabric Tongue Tear Strength	90 lbs	41 kg
Fabric Adhesion	12 lbs/in	10.8 kg/5cm
Colour	Orange	
Flotation Material / Shape	Closed cell polyethylene foam/cylindrical	
Fold points	Every 5 feet	Every 1.52 m
Boom Weight	1.5 lbs/ft	2.2 kg/m
Reserve Buoyancy	11 lbs/ft	16 kg/m
Reserve Buoyancy/Weight Ratio	7.3:1	
Ballast	9/32 in (7.1 mm) Grade 30 galvanised chain	
Ballast Weight	0.67 lbs/ft	1.0 kg/m
Ballast Tensile Strength	5200 lbs	2365 kg
Chain Pocket	Single layer, fully enclosed	

All above values are nominal and subject to change without notice.