



**Canadyne Contractor Boom 8/10 22P**

Part No. BMCOPP08.10.22IN.50

<b><u>SPECIFICATION</u></b>	<b><u>IMPERIAL</u></b>	<b><u>METRIC</u></b>
Boom Height	18 in	457 mm
Freeboard	8.0 in	203 mm
Draft	10.0 in	254 mm
Standard Length	51 ft	15.75 m
End Connectors	ASTM-standard extruded aluminum connectors	
Skirt Material	PVC-coated polyester	
Skirt Weight	22 oz/yd <sup>2</sup>	750 g/m <sup>2</sup>
Fabric Strip Tensile Strength	310 lbs/in	141 kg
Fabric Tongue Tear Strength	90 lbs	41 kg
Fabric Adhesion	12 lbs/in	10.8 kg/5cm
Colour	Orange	
Flotation Material / Shape	Closed cell polyethylene foam/cylindrical	
Fold points	Every 5 feet	Every 1.52 m
Boom Weight	2.0 lbs/ft	1.52 kg/m
Reserve Buoyancy	20 lbs/ft	30 kg/m
Reserve Buoyancy/Weight Ratio	10:1	
Ballast	5/16 in (8.3 mm) Grade 30 galvanised chain	
Ballast Weight	1.12 lbs/ft	1.7 kg/m
Ballast Tensile Strength	8000 lbs	3640 kg
Chain Pocket	Single layer, fully enclosed	

All above values are nominal and subject to change without notice.