



Canadyne FenceBoom 24

Part No. BMFBPP24.22.50ER

<u>SPECIFICATION</u>	<u>IMPERIAL</u>	<u>METRIC</u>
Boom Height	24 in	610 mm
Freeboard	6.6 in	168 mm
Draft	17.4 in	442 mm
Standard Length	50 ft	15.25 m
End Connectors	ASTM or Shotgun H-standard extruded aluminum connectors	
Skirt Material	PVC-coated polyester	
Skirt Weight	22 oz/yd ²	750 g/m ²
Colour	Orange standard, others available	
Flotation Material / Shape	Rectangular closed cell, flexible, oil resistant polyethylene foam	
Boom Weight	1.7 lbs./ft	2.6 kg/m
Buoyancy	3.9 lbs./ft	5.8 kg/m
Buoyancy/Weight Ratio	2.3:1	
Waterline Beam	2 in	5.1 cm
Ballast	9/32 in (7.1 mm) Grade 30 galvanised chain	
Ballast Weight	0.67 lbs./ft	1.0 kg/m
Ballast Tensile Strength	5200 lbs.	2365 kg
Chain Pocket	Fully enclosed, single layer	
Top Tension Member	Optional PVC coated galvanized steel cable	

All above values are nominal and subject to change without notice.