



Canadyne Technologies Inc.

Canadyne FlashBoom 12/18 26U

Part No. BMFLUP12.18.26.82ER

<u>SPECIFICATION</u>	<u>IMPERIAL</u>	<u>METRIC</u>
Boom Height	30.0 in	762 mm
Freeboard	12.0 in	305 mm
Draft	18.0 in	457 mm
Boom Length	82 ft	25 m
End Connectors	ASTM F962-99 extruded marine grade aluminum connector	
Fabric	Urethane-coated polyester	
Fabric Weight	26 oz/yd ²	885 g/m ²
Colour	Orange standard, others available	
Flotation Material / Shape	Self-inflating air chambers/cylindrical	
Internal Air Chamber Length	10 ft	3.05 m
Separation of Chambers	Internal bulkheads, smooth exterior	
Self-Inflation Method	One way air check valve, removable	
Boom Weight	2.0 lbs./ft	3.0 kg/m
Reserve Buoyancy	47 lbs./ft	70 kg/m
Reserve Buoyancy/Weight Ratio	23.5:1	
Ballast	9/32 in. (7.1 mm) Grade 30 galvanised chain	
Ballast Weight	0.67 lbs./ft	1.0 kg/m
Ballast Tensile Strength	5000 lbs.	2275 kg
Chain Pocket	Single layer, fully enclosed	

All above values are nominal and subject to change without notice.