



Canadyne MarineTruck 18 Specifications

	Imperial	Metric
Overall length:	18 ft	5.5 m
Beam:	8 ft	2.4 m
Freeboard, unladen forward:	33 in	0.84 m
Freeboard, unladen aft:	25 in	0.64 m
Draft, unladen:	7 in	0.18 m
Draft, laden:	15 in	0.38 m
Deck width:	7.5 ft	2.29 m
Deck length:	14.5 ft	4.42 m
Deck to gunwale:	25 in	0.64
Payload, sheltered Waters:	2,000 lbs	909 kg
Payload, sea Conditions:	1000 lbs	455 kg
Weight, bare hull:	1100 lbs	500 kg
Total Buoyancy, built in:	5,000 lbs	2273 kg

Hull: Welded marine grade aluminum plate and extrusions with plate gussets and stiffeners at all high stress points.

Structure: Hull structure has heavy-duty box frame chassis formed from plate and angle beams. Chassis is welded to bottom and deck.

Deck: Coated with Armor Guard, non-skid deck coating or checkerplate, stiffened.

Sides: Marine grade aluminum.

Buoyancy: Watertight bulkheads.

Ramp: Aluminum plate on the outside and checkerplate on the inside. Fully stiffened.

Transom will be made from aluminum plate. Insides of the port, starboard, stern and bow vertically braced with angle. The bottom of the boat stiffened from bow to stern.

Console/Instrumentation: Many styles/options available.

Electrical: Standard Package included.

Power: Outboard, I/O, diesel, available.

All dimensions and specifications are nominal and subject to change without notice